## In the claims:

Delete original claims 1 through 9 and substitute therefore the following new claims 10 through 21:

- 10. A method for producing town gas comprising the steps of;
  - (A) preparing dimethyl ether as feed stock;
  - (B) evaporating said dimethyl ether and;
- (C) reforming said dimethyl ether with steam in the presence of catalyst to produce reformed gas containing mainly methane.
- 11. A method for producing town gas according to claim 10, in which the quantity of said steam on reforming is within 10/1 to 0.5/1 molar ratio of steam/dimethyl ether.
- 12. A method for producing town gas according to claim 10, in which the temperature for catalytic reforming of said dimethyl ether is within 200 °C to 600 °C.
- 13. A method for producing town gas according to claim 10, in which said dimethyl ether is supplied serially to adiabatic fixed bed reactors through cooling means installed between said reactors.
- 14. A method for producing town gas according to claim 10, in which said dimethyl ether is divided and a divided portion thereof is serially supplied to adiabatic fixed bed reactors, and simultaneously supplying the remaining portion of said divided dimethyl ether to at least a subsequent one of said reactors.
- 15. A method for producing town gas according to claim 10, in which said dimethyl ether is reformed with a reactor selected from the group consisting of a fluidized bed reactor and a multi-tubular reactor.

- 16. A method for producing town gas according to claim 10, in which carbon dioxide by-produced by said reforming of said dimethyl ether is removed from said reformed gas after reforming said dimethyl ether.
- 17. A method for producing town gas according to claim 16, in which said carbon dioxide is removed from said reformed gas by absorption by a solution selected from the group consisting of a aqueous alkanolamine solution and a heated aqueous potassium carbonate solution.
- 18. A method for producing town gas according to claim 16, in which said carbon dioxide is removed from said reformed gas by adsorption by a pressure swinging method.
- 19. A method for producing town gas according to claim 16, in which said carbon dioxide is removed from said reformed gas by selective separation by membrane.
- 20. A method for producing town gas according to claim 16, in which hydrogen, carbon monoxide and carbon dioxide, which are by-produced on said reforming process, are methanized.
- 21. A method for producing town gas according to claim 10, in which a portion of said dimethyl ether is added to said reformed gas as carburant.

## REMARKS

This Amendment corrects grammatical errors in the specification and corrects indefinite language in the original claims. It is believed that the foregoing amendments will greatly facilitate examination.

A marked up version of the amended paragraphs of the specification and claims follows in the attached appendix.

Respectfully submitted,

CAROTHERS AND CAROTHERS

Floyd B. Carothers

Attorney for Shinya Ishigaki et al.

445 Fort Pitt Blvd., Suite 500

Pittsburgh, PA 15219

FBC:jkc (412)471-3575 (412)281-2180 FAX